

TP-LINK JetStream TL-SG3210 10-port 8x Gigabit RJ45 2x Gigabit SFP L2 managed mrežno stikalo switch

Kategorija: [Stikala](#)
Dobavljivost: **predvidena dobava 24.08.2026**
Šifra: **87343**

Cena: 118,36€ ~~129,12€~~



(slika je simbolična)

Kratek opis

Podrobno o izdelku:

Proizvajalčeva koda	SG3210
EAN koda:	6935364098490
Proizvajalec:	TP-LINK
razprodaja	No
Namestitev:	namizni
Vrsta stikala:	Managed
Standard:	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE 802.3ad, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1x, IEEE 802.1p
Vmesniki:	8x gigabit RJ45, 2x Gigabit SFP, 1x RJ45 Console Port, 1 Micro-USB Console Port
Zmogljivost:	Prepustnost: 20 Gbps Število paketov na sekundo: 14,9 Mbps

Quality of Service

Support 802.1p CoS/DSCP priority
Support 4 priority queues
Queue scheduling: SP, WRR, SP+WRR
Port/Flow- based Rate Limiting
Voice VLAN

L2 Features

IGMP Snooping v1/v2/v3
MLD v1/v2 Snooping
802.3ad LACP (Up to 8 aggregation groups, containing 8 ports per group)
Spanning Tree STP/RSTP/MSTP
Port isolation
BPDU filtering/guard
TC/Root protect
Loop back detection
802.3x Flow Control
LLDP/LLDP-MED
DHCP VLAN Relay
L2PT

VLAN

Supports up to 4K VLANs simultaneously (out of 4K VLAN IDs)
MAC/Protocol-based VLAN
GARP/GVRP
VLAN VPN (QinQ)
Management VLAN configuration

Access Control List

L2~L4 package filtering based on source and destination MAC address, IP address, TCP/UDP ports,
802.1p, DSCP, protocol and VLAN ID;
Time Range Based

Security

IP-MAC-Port-VID Binding
AAA
DHCP Snooping
IEEE 802.1X Port/MAC Based authentication, Radius, Guest VLAN
DoS Defend

Programske funkcije: Dynamic ARP inspection (DAI)

SSH v1/v2
SSL v2/v3/TLSv1
Port Security
Broadcast/Multicast/Unknown-unicast Storm Control
PPPoE

IPv6

Dual IPv4/IPv6 stack
Multicast Listener Discovery (MLD) Snooping
IPv6 neighbor discovery (ND)
Path maximum transmission unit (MTU) discovery
Internet Control Message Protocol (ICMP) version 6
TCPv6/UDPv6

IPv6 Applications

DHCPv6 Client
Ping6
Tracert6
Telnet(v6)
IPv6 SNMP
IPv6 SSH
IPv6 SSL
Http/Https
IPv6 TFTP

Management

Web-based GUI and CLI management
SNMP v1/v2c/v3, compatible with public MIBs and TP-LINK private MIBs
RMON (1, 2, 3, 9 groups)
DHCP/BOOTP Client, DHCP Snooping, DHCP Option82
CPU Monitoring
Port Mirroring
Dual Image
Time Setting: SNTP
Integrated NDP/NTDP feature
Firmware Upgrade: TFTP & Web
System Diagnose: VCT
SYSLOG & Public MIBS

Poraba: do 8,38 W
Dimenzije: 294 (Š) x 180 (G) x 44 (V) mm
Garancija: 24 mesecev
Vsebina paketa: stikalo, napajalni kabel, rack nosilci, gumijaste noge

Tehnične Specifikacije

Število priklonov: 8
Hitrost: 10/100/1000 Mbps + SFP 1.25 Gbps