

Datum: 12.08.2026

Davčna št.: si20355289
Telefon: 040 426 026
E-mail: prodaja@alt-store.si
WWW: www.altstore.si



TP-LINK JetStream TL-SG2210MP 10-port 8x Gigabit PoE+ RJ45 2x Gigabit SFP Smart mrežno stikalo switch

Kategorija: [Stikala](#)
Dobavljivost: **predvidena dobava 19.08.2026**
Šifra: **176335**

Cena: 173,65€ ~~189,44€~~

(slika je simbolična)

Kratek opis

Podrobno o izdelku:

Proizvajalčeva koda SG2210MP
EAN koda: 6935364030674
Proizvajalec: TP-LINK
razprodaja: No
Namestitev: rack / namizni
Vrsta stikala: Managed
Standard: IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3ad, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1x, IEEE 802.1p
Vmesniki: 8x 10/100/1000 Mbps RJ45, 2x 100/1000 Mbps SFP
Hitrost: 10/100/1000Mbps
PoE: 8x PoE+ 802.3at/af, do 30W na port, skupno do 150W

Kakovost storitev:

- 802.1p CoS/DSCP priority
- 8 priority queues
- Priority Schedule Mode
- SP (Strict Priority)
- WRR (Weighted Round Robin)
- Queue Weight Config
- Bandwidth Control
- Port/Flow based Rating Limit
- Smoother Performance
- Storm Control
- Multiple Control Modes(kbps/ratio)
- Broadcast/Multicast/Unknown-Unicast Control

L2 in L2+ Lastnosti:

- DHCP Relay
- DHCP VLAN Relay
- DHCP L2 Relay
- Link Aggregation
- Static link aggregation
- 802.3ad LACP
- Up to 8 aggregation groups and up to 8 ports per group
- Spanning Tree Protocol
- 802.1D STP
- 802.1w RSTP
- 802.1s MSTP
- STP Security: TC Protect, BPDU Filter/Protect, Root Protect
- Loopback Detection
- Flow Control
- 802.3x Flow Control
- Mirroring
- Port Mirroring
- CPU Mirroring
- One-to-One
- Many-to-One
- Flow-Based
- Ingress/Egress/Both
- Device Link Detect Protocol (DLDP)
- 802.1ab LLDP/ LLDP-MED

L2 Multicast

- IPv4, IPv6 shared multicast groups (511 groups max.)
- IGMP Snooping
- IGMP v1/v2/v3 Snooping
- Fast Leave
- IGMP Snooping Querier
- Static Group Config
- Multicast VLAN Registration (MVR)
- Multicast Filtering
- MLD Snooping
- MLD v1/v2 Snooping
- Fast Leave
- MLD Snooping Querier
- Static Group Config
- Limited IP Multicast (256 profiles and 16 entries per profile)

IPv6 Podpora

- IPv6 Dual IPv4/IPv6
- Multicast Listener Discovery (MLD) Snooping
- IPv6 neighbor discovery (ND)
- Path maximum transmission unit (MTU) discovery
- Internet Control Message Protocol (ICMP) version 6
- TCPv6/UDPv6
- IPv6 applications
- DHCPv6 Client
- Ping6
- Tracert6
- Telnet (v6)
- IPv6 SNMP
- IPv6 SSH
- IPv6 SSL
- Http/Https
- IPv6 TFTP

VLAN

- VLAN Group
- Max. 4K VLAN Groups
- 802.1Q tag VLAN
- MAC VLAN
- Protocol VLAN
- GVRP

Programske funkcije:

- Voice VLAN

Seznam za nadzor dostopa - 230 vnosov

- Time-Range
- Time Slice
- Week Time-Range
- Absolute Time-Range
- Holiday
- Time-based ACL
- MAC ACL
- Source MAC
- Destination MAC
- VLAN ID
- User Priority
- Ether Type
- IP ACL
- Source IP
- Destination IP
- IP Protocol
- TCP Flag
- TCP/UDP Source Port
- TCP/UDP Destination Port
- DSCP/IP TOS
- IPv6 ACL
- Combined ACL
- Rule Operation
- Permit/Deny
- Policy Action
- Mirror
- Rate Limit
- Redirect
- QoS Remark
- ACL Rules Binding
- Port Binding
- VLAN Binding
- Actions for flows
- Mirror (to supported interface)
- Redirect (to supported interface)
- Rate Limit
- QoS Remark

Varnost:

- AAA
- 802.1X
- Port based authentication
- MAC (Host) based authentication
- Authentication Method includes PAP/EAP-MD5
- MAB
- Guest VLAN
- Support Radius authentication and accountability
- IP/IPv6-MAC Binding
- 512 Binding Entries
- DHCP Snooping
- DHCPv6 Snooping
- ARP Inspection
- ND Detection
- IP Source Guard
- 253 Entries
- Source IP+Source MAC
- IPv6 Source Guard
- 183 Entries
- Source IPv6 Address+Source MAC
- DoS Defend
- Static/Dynamic/Permanent Port Security
- Up to 64 MAC addresses per port
- Broadcast/Multicast/Unicast Storm Control
- kbps/ratio control mode
- Port Isolation
- Secure web management through HTTPS with SSLv3/TLS 1.2
- Secure Command Line Interface (CLI)
- management with SSHv1/SSHv2
- IP/Port/MAC based access control

MIBs

- MIB II (RFC1213)
- Bridge MIB (RFC1493)
- P/Q-Bridge MIB (RFC2674)
- Radius Accounting Client MIB (RFC2620)
- Radius Authentication Client MIB (RFC2618)
- Remote Ping, Traceroute MIB (RFC2925)
- Support TP-Link private MIBs
- RMON MIB(RFC1757, rmon 1.2,3,9)

Dimenzije: 294 x 180 x 44 mm
Garancija: 24 mesecev
Vsebina paketa: Stikalo, napajalni kabel, navodila, rack nosilci, gumijaste nogice

Tehnične Specifikacije

Število priklonov: 8
Hitrost: 10/100/1000 Mbps + SFP 1.25 Gbps