

Datum: 03.07.2026

Davčna št.: si20355289

Telefon: 040 426 026

E-mail: [prodaja@alt-store.si](mailto:prodaja@alt-store.si)WWW: [www.altstore.si](http://www.altstore.si)

## Ubiquiti gigabitno Layer 2 stikalo USW-48

Kategorija: [Stikala](#)Dobavljivost: **predvidena dobava 09.07.2026**Šifra: **219059****Cena: 419,78€** ~~443,74€~~

(slika je simbolična)

## Kratek opis

Layer 2 stikalo z (48) vrati GbE RJ45 in (4) vrati 1G SFP.

Stikalo 48 (USW 48) je popolnoma upravljano stikalo brez ventilatorja z (48) vrati GbE RJ45 in (4) vrati 1G SFP.

Vsestranski USW 48 zagotavlja gigabitne povezave do ethernetnih naprav, hkrati pa zagotavlja možnosti povezave navzgor za gigabitna vlakna, primerne za podjetniško omrežje.

Stikalo ponuja tudi obsežen nabor preklopnih protokolov nivoja 2, vključno z načini delovanja, specifičnimi za vrata (preklapljanje, zrcaljenje ali združevanje), in ima 1,3-palčni barvni zaslon na dotik LCM, ki jedrnato prikazuje vpoglede v sistem ključnih in povezav.

To stikalo je lahko tudi spremljati ali konfigurirati od koder koli z zmogljivo, intuitivno spletno aplikacijo UniFi Network in mobilno aplikacijo.

### Lastnosti:

(1) 1,3-palčni barvni zaslon na dotik LCM z upravljanjem stikala AR

(48) vrat GbE RJ45

(4) vrata 1G SFP

Tiho hlajenje brez ventilatorja

### Specifikacije:

Mechanical	
Dimensions	442.4 x 285 x 43.7 mm (17.42 x 11.22 x 1.72")
Weight	Without Mount: 3.9 kg (8.6 lb)
	With Mount: 3.99 kg (8.8 lb)
Enclosure Characteristics	SGCC Steel
Hardware	
Total Non-Blocking Line Rate	52 Gbps

Max. Power Consumption	40W
Forwarding Rate	77.376 Mpps
Power Method	Universal AC Input: 100-240VAC, 50/60 Hz
Power Supply	AC/DC, Internal, 60W
Supported Voltage Range	100 - 240VAC
Networking Interfaces	(48) 10/100/1000 Mbps Ethernet RJ45 Ports
	(4) 1 Gbps SFP Ports
Management Interface	Ethernet In-Band
Modes	SMB Layer 2 Gigabit Ethernet Switch
Operating Temperature	-15 to 40° C (5 to 104° F)
Operating Humidity	10 - 90% Noncondensing
Certifications	CE, FCC, IC
LEDs	
System	(1) Bootup Animation: Bootup in Progress
	Firmware Upgrade Icon: Firmware Upgrading
	Steady White: Factory Defaults, Awaiting Adoption
	Steady Blue: Device is Adopted
Ethernet	Green: 1G, Amber: 10/100 Mbps
SFP	Green: 1G

Uradna stran proizvajalca: <https://eu.store.ui.com/collections/unifi-network-routing-switching/products/unifi-switch-48>

## Tehnične Specifikacije

Hitrost: 10/100/1000 Mbps