

Datum: 21.09.2026

Davčna št.: si20355289

Telefon: 040 426 026

E-mail: prodaja@alt-store.siWWW: www.altstore.si

Ubiquiti stikalo 48 port PoE USW-Pro-48-POE

Kategorija: [Stikala](#)Dobavljivost: **predvidena dobava 28.09.2026**Šifra: **219049****Cena: 1.153,50€** ~~1.219,34€~~

(slika je simbolična)

Kratek opis

48-portno stikalo s (40) 802.3at PoE+ porti, (8) 802.3bt PoE++ porti in (4) 10 GB SFP+ porti.

Specifikacije:

(8) Gigabit RJ45 802.3bt PoE++ vrata

(40) Gigabit RJ45 802.3at PoE+ vrata

(4) 10G SFP+ vrata

Layer 2 and Layer 3 features

600W maximum PoE power

UniFi SmartPower RPS DC input

Near-silent cooling

1.3" zaslon na dotik

Managed by UniFi Network Controller

Dimenzije: 442.4 x 399.6 x 43.7 mm (17.42 x 15.73 x 1.72")

Teža: 6.25 kg

Teža z okvirjem za Rack montažo: 6.34 kg

Spletna stran izdelka: KLIK

Mechanical	
Dimensions	442.4 x 399.6 x 43.7 mm (17.42 x 15.73 x 1.72")
Weight	6.25 kg (13.78 lb)
With Rackmount Brackets	6.34 kg (13.98 lb)
Interfaces	(48) 10/100/1000 RJ45 Ports
Networking	(4) 1/10G SFP+ Ethernet Ports

Management	Ethernet In-Band
Power Method	
Universal Input	100-240VAC/50-60 Hz
USP RPS DC Input	52VDC, 11.54A; 11.5VDC, 5.22A
Power Supply	AC/DC, Internal, 660W
Supported Voltage Range	100 to 240VAC
Max. Power Consumption (Excluding PoE Output)	60W
LEDs	
System	Status
RJ45 Data Ports	PoE; Speed/Link/Activity
SFP Data Ports	Link/Activity
ESD/EMP Protection	Air: ± 16 kV, Contact: ± 12 kV
Shock and Vibration	ETSI300-019-1.4 Standard
Operating Temperature	-5 to 40° C (23 to 104° F)
Operating Humidity	10 to 90% Noncondensing
Certifications	CE, FCC, IC
Sound Level*	
25% PoE Load, 25° C Room Temperature	0.9 dBr
50% PoE Load, 25° C Room Temperature	7.3 dBr
100% PoE Load, 40° C	22.5 dBr
PoE	
PoE Interfaces	
Ports 1-40	POE+ IEEE 802.3af/at, (pins 1, 2+; 3, 6-)
Ports 41-48	60W PoE++ IEEE 802.3bt, (Pair A 1, 2+; 3, 6-) (Pair B 4, 5+; 7, 8-)
Max. PoE Wattage per Port by PSE	
802.3at	32W
802.3bt	64W
Voltage Range 802.3af Mode	44-57V
Voltage Range 802.3at Mode	50-57V

Uradna stran proizvajalca: <https://store.ui.com/collections/unifi-network-routing-switching/products/usw-pro-48-poe>

Tehnične Specifikacije

Število priklonov: 8

Ohišje: Vgradno